THE 67TH INTERNATIONAL



OPEN READINGS

CONFERENCE FOR STUDENTS OF PHYSICS AND NATURAL SCIENCES

BOOK OF ABSTRACTS

2024



Editors:

Martynas Keršys Rimantas Naina Vincentas Adomaitis Emilijus Maskvytis

Cover and Interior Design:

Goda Grybauskaitė

Vilnius University Press 9 Saulėtekio Av., III Building, LT-10222 Vilnius info@leidykla.vu.lt, www.leidykla.vu.lt/en/ www.knygynas.vu.lt, www.journals.vu.lt

Bibliographic information is available on the Lithuanian Integral Library Information System (LIBIS) portal www.ibiblioteka.lt ISBN 978-609-07-1051-7 (PDF)

© Vilnius University, 2024

MICROSTRUCTURING OF HIGH BANDGAP MATERIALS USING FEMTOSECOND UV LASER PULSES FOR MULTI-LEVEL DIFFRACTIVE OPTICAL ELEMENTS

Vitalija Smirnovaitė¹, Dominyka Stonytė², Domas Paipulas³

¹Laser Research Center, Faculty of Physics, Vilnius University, Vilnius LT-10223, Lithuania vitalija.smirnovaite@ff.stud.vu.lt

Micro-structuring of materials is one of the most widely applied fields in science and industry. The main objective of surface structuring is to tailor the properties of the outer layer of a material to meet specific functional, aesthetic, or performance requirements [1]. The complex interplay between laser characteristics and dielectric materials provides insight into how specific laser parameters shape the structural and functional properties of these materials. The diffraction limited focus point size is directly proportional to the wavelength, so a smaller spot size leads to the precision. Thanks to the short UV wavelength, it is possible to ablate materials with high precision and obtain a smooth surface morphology [2]. When the pulse is short, the laser energy is very intense on the target, resulting in a cleaner, more precise ablation process and ability for highly accurate control of the depth of the infringement [3].

The precision and smoothness is a must for the fabrication of DOE-phase micro structured elements. One of the most commonly used diffractive elements is the Fresnel zone plate, but due to the limited resolution and the size of the possible structure, researchers have developed a new diffractive element, the photon sieve [4]. It consists of a series of pinholes of different depths spread over the entire Fresnel zone plate. Photon sieves can be used to obtain a sharper focus, which is not dependent on the width of the zone area buton the dimensions of the pinholes [5].

This article describes the influence of laser parameters on the micro-structuring of fused quartz by single pulses of

"PHAROS

" femtosecond laser radiation. The results are analyzed, the dependences of depth, width and volume on the pulse energy are investigated and the most suitable parameters for fabricating photon sieves are selected. Five photon sieves of different periods (T = 4,5,6,8 and $10\mu m$) have been created with a focal length of 9 mm.




Fig. 1. a) the depth of pinholes illustrated by a graph, b) Photon sieve image by profilometer, c) Efficiency of different periods photon sieves.

The highest efficiency obtained was for a $T=4\mu m$ period photon sieve, which was 2.06%. Compared to the studies using the same elemental design method, the efficiency value is 1.75 times higher ($\eta=1,18\%$ [5]). Also, this effiency is achieved with a focal length of 9 mm, that is 17 times smaller (f=150mm [5]).

Mangirdas Malinauskas, Albertas Žukauskas, Satoshi Hasegawa, Yoshio Hayasaki, Vygantas Mizeikis, Ričardas Buividas, and Saulius Juodkazis.
 Ultrafast laser processing of materials: From science to industry, 8 2016.
 J Zhang, K Sugioka, and K Midorikawa. Laser-induced plasma-assisted ablation of fused quartz using the fourth harmonic of a nd+:yag laser, 1998.

^[2] J Zhang, K Sugioka, and K Midorikawa. Laser-induced plasma-assisted ablation of fused quartz using the fourth harmonic of a nd+:yag laser, 1998.

[3] P. Balling and J. Schou. Femtosecond-laser ablation dynamics of dielectrics: Basics and applications for thin films. Reports on Progress in Physics, 76,

^[4] Wenbo Jiang, Song Hu, Lixin Zhao, Wei Yan, and Yong Yang. Design and application of phase photon sieve. Optik, 121:637–640, 4 2010.

^[5] Matthew N. Julian, David G. MacDonnell, and Mool C. Gupta. Fabrication of photon sieves by laser ablation and optical properties. Optics Express, 25:31528, 12 2017.