THE 67TH INTERNATIONAL

OPEN READINGS



CONFERENCE FOR STUDENTS OF PHYSICS AND NATURAL SCIENCES

BOOK OF 2024 ABSTRACTS



VILNIUS UNIVERSITY PRESS

Editors:

Martynas Keršys Rimantas Naina Vincentas Adomaitis Emilijus Maskvytis

Cover and Interior Design:

Goda Grybauskaitė

Vilnius University Press 9 Saulėtekio Av., III Building, LT-10222 Vilnius info@leidykla.vu.lt, www.leidykla.vu.lt/en/ www.knygynas.vu.lt, www.journals.vu.lt

Bibliographic information is available on the Lithuanian Integral Library Information System (LIBIS) portal www.ibiblioteka.lt ISBN 978-609-07-1051-7 (PDF)

© Vilnius University, 2024

ACRYLIC RESINS FOR LASER 3D LITHOGRAPHY OF HIGHLY-POROUS MICROSTRUCTURES

Saulė Petrauskaitė¹, Ioanna Angeliki Petsi¹, Arūnas Čiburys¹, Antanas Butkus¹, Karolis Galvanauskas¹, Mangirdas Malinauskas¹

¹Laser Research Center, Faculty of Physics, Vilnius University, Lithuania saule.petrauskaite@ff.stud.vu.lt

Inertial Confinement Fusion (ICF) is a potential way to produce energy by using high-power lasers to compress a fuel capsule. Low-density foams find common use as targets in experiments involving laser-plasma interactions because they can be converted into large-volume homogeneous plasmas. The major advantage of utilizing foam targets lies in their swift transition from a structured solid material to a nearly uniform plasma under intense radiation [1]. To produce such low-density foams lithography techniques are used. Particularly in this experiment, two photon polymerization that provides significant advantage in print resolution in creating three-dimensional microstructures [2].

In this research, our task is to create foams comprising exclusively of light elements for example hydrogen, carbon, and oxygen. For this purpose, we employ acrylic resins. Highly-porous microstructures play a crucial role in ICF, because they serve multiple functions, such as smooth the laser beam inhomogeneities, enhance the laser absorption as well as increase the ablation loading in a layered target configuration. However, a problem arises when using foams which contain only light elements as they tend to shrink during the two-photon polymerization process and structure development. Therefore extensive and varied research is necessary to identify the most suitable resin for low-density foams. This study focuses on investigating the optimal acrylic resin and photoinitiator for the development of low-density highly-porous microstructures, intended for application in ICF.

^[1] Tikhonchuk, V. T., Gu, Y. J., Klimo, O., Limpouch, J., & Weber, S. Studies of laser-plasma interaction physics with low-density targets for direct-drive inertial confinement schemes. Matter and Radiation at Extremes 4.4 (2019): 1.5090965

^[2] Wang, H., Zhang, W., Ladika, D., Yu, H., Gailevičius, D., Wang, H., Pan, C., Nair, P. N. S., Ke, Y., Mori, T., Chan, J. Y. E., Ruan, Q., Farsari, M., Malinauskas, M., Juodkazis, S., Gu, M., & Yang, J. K. W. Two Photon Polymerization Lithography for optics and Photonics: Fundamentals, materials, technologies, and applications. Advanced Functional Materials 33.39 (2023): 202214211